

## PRODUCT SPECIFICATION

### SUPERDISPERSANT-25

Superdispersant-25 is a high performance, non-flammable, non-toxic treatment for oil spills. It may be used diluted or concentrated, applied from the air, vessels or by manual sprayers.

Density@20°C:	0.95-1.05 kg/l
pH:	5.5-7.5
Flash Point:	Non-flammable
Viscosity:	Less than 250 mPa s @ 0°C
Appearance:	Clear
Colour:	Slight yellow

Efficiency Index:	Type 2	Type 3
2000 mPa s fuel oil	45%	90%
500 mPa s fuel oil	N/A	65%

Superdispersant-25 is available in 200 litre/kilo as standard. In this packaging a minimum shelf life of 5 years is given, if the drums are stored unopened and in cool, dry conditions. Other packaging is available on request.

Superdispersant-25 is manufactured by a MCAA (Marine and Coastal Access Act 2009) approved product facility under ISO9001 and ISO15001 quality standards.

#### **OIL SLICK DISPERSANTS LIMITED**

Beck Cottage, Main Street, Elvington, York, England, YO41 4AG

Tel: +44 (0)1904 607910 Fax: +44 (0)1904 607911

e-mail [sales@oilslickdispersants.co.uk](mailto:sales@oilslickdispersants.co.uk)