

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Superdispersant-25[®]
Product code : PS8011

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

No additional information available

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Oil Slick Dispersants Ltd
Beck Cottage, Main Street, Elvington
YO41 4AG York – North Yorkshire
United Kingdom
+44 1904 607910
paul@oilslickdispersants.co.uk - www.oilslickdispersants.co.uk

1.4. Emergency telephone number

Emergency number : +44 1904 607910

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Repeated exposure, Category 2	H373

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008

Hazard pictograms (CLP)



Signal word (CLP)

: Warning

Contains

: Butyl Glycol

Hazard statements (CLP)

: H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H373 - May cause damage to organs through prolonged or repeated exposure.

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP) : P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Butyl Glycol substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0	10 – 20	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373
Sodium Dioctyl Sulphosuccinate	CAS-No.: 577-11-7 EC-No.: 209-406-4	0.6 – 10	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Move the affected person away from the contaminated area and into the fresh air. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Loosen tight clothing such as a collar, tie, belt or waistband. Call a poison center or a doctor if you feel unwell.

First-aid measures after skin contact : Wash immediately with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing.

First-aid measures after eye contact : Rinse immediately with plenty of water (for at least 15 minutes). Remove any contact lenses and open eyelids wide apart. Seek medical attention if ill effect or irritation develops. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

First-aid measures after ingestion : Rinse mouth out with water. Do NOT induce vomiting. If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. If unconscious, place in the recovery position and seek medical advice. Loosen tight clothing such as a collar, tie, belt or waistband. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Butyl Glycol (111-76-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Butoxyethanol
IOEL TWA	98 mg/m ³
IOEL TWA [ppm]	20 ppm
IOEL STEL	246 mg/m ³
IOEL STEL [ppm]	50 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Austria - Occupational Exposure Limits	
Local name	2-Butoxyethanol (Butylglykol; Ethylenglykolmonobutylether)
MAK (OEL TWA)	98 mg/m ³
MAK (OEL TWA) [ppm]	20 ppm
MAK (OEL STEL)	200 mg/m ³ (4x 30(Miw) min)
MAK (OEL STEL) [ppm]	40 ppm (4x 30(Miw) min)
Remark	H
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	2-Butoxyéthanol # 2-Butoxy-ethanol
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	2-Бутоксиетанол
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	Кожа (възможна е значителна резорбция чрез кожата); • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)

Butyl Glycol (111-76-2)	
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	2-Butoksietanol; etilen-glikol monobutil-eter; butilov celosolv
GVI (OEL TWA) [1]	98 mg/m ³
GVI (OEL TWA) [2]	20 ppm
KGVI (OEL STEL)	246 mg/m ³
KGVI (OEL STEL) [ppm]	50 ppm
Remark	Direktiva: 2000/39/EZ. Napomena: Koža (razvrstana kao tvar koja nadražuje kožu (H315))
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Cyprus - Occupational Exposure Limits	
Local name	2-Βουτοξυαιθανόλη
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

OEL STEL [ppm]	50 ppm
Remark	δέρμα
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)

Czech Republic - Occupational Exposure Limits

Local name	2-Butoxyethanol (Butylcellosolv; Ethylenglykolmonobutylether)
PEL (OEL TWA)	100 mg/m ³
PEL (OEL TWA) [ppm]	20 ppm
NPK-P (OEL C)	200 mg/m ³
NPK-P (OEL C) [ppm]	41 ppm
Remark	D - při expozici se významně uplatňuje pronikání faktoru kůží, I - dráždí sliznice (oči, dýchací cesty), respektive kůži, B - u látky je zaveden biologický expoziční test (BET) v moči nebo krvi.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)

Czech Republic - Biological limit values

Local name	2-Butoxyethanol (Butylcellosolv, Ethylenglykolmonobutylether)
BLV	200 mg/g creatinine Ukazatel: Butoxyoctová kyselina - Biologicky vzorek: moči - Doba odběru: konec směny na konci 0.17 mmol/mmol Creatinine Ukazatel: Butoxyoctová kyselina - Biologicky vzorek: moči - Doba odběru: konec směny na konci
Regulatory reference	Vyhláška č. 107/2013 Sb. (kterou se mění vyhláška č. 432/2003 Sb.)

Denmark - Occupational Exposure Limits

Local name	Butylglycol (2-Butoxyethanol; Butylcellosolve; Ethylenglykolmonobutylether)
OEL TWA [1]	98 mg/m ³
OEL TWA [2]	20 ppm

Butyl Glycol (111-76-2)

Remark	E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden)
Regulatory reference	BEK nr 2203 af 29. november 2021

Estonia - Occupational Exposure Limits

Local name	2-butoksüetanol (o-butüületüleenglükool, etüleenglükoolmono-butüüleeter, butüülsellosolv)
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	A (Naha kaudu kergesti imenduv aine), S (Sensibiliseeriv aine)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
Finland - Occupational Exposure Limits	
Local name	2-Butoksietanoli
HTP (OEL TWA) [1]	98 mg/m ³
HTP (OEL TWA) [2]	20 ppm
HTP (OEL STEL)	250 mg/m ³
HTP (OEL STEL) [ppm]	50 ppm
Remark	lho
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	2-Butoxyéthanol (Butylglycol)
VME (OEL TWA)	49 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	246 mg/m ³
VLE (OEL C/STEL) [ppm]	50 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-Butoxyethanol
AGW (OEL TWA) [1]	49 mg/m ³
AGW (OEL TWA) [2]	10 ppm
Peak exposure limitation factor	2(I)
Remark	EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Butyl Glycol (111-76-2)

Germany - Biological limit values (TRGS 903)

Local name	2-Butoxyethanol
Biological limit value	150 mg/g creatinine Parameter: Butoxyessigsäure (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende, c) bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten - Festlegung/Begründung: 11/2016 DFG
Regulatory reference	TRGS 903

Gibraltar - Occupational Exposure Limits

Local name	2-Butoxyethanol
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	Skin
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)

Greece - Occupational Exposure Limits

Local name	Βουτοξυ-αιθανόλη, 2-
OEL TWA	120 mg/m ³
OEL TWA [ppm]	25 ppm
Remark	Η ένδειξη «δέρμα» στις οριακές τιμές επαγγελματικής έκθεσης επισημαίνει το ενδεχόμενο σημαντικής διείσδυσης μέσω του δέρματος.
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους

Hungary - Occupational Exposure Limits

Local name	2-BUTOXIETANOL
AK (OEL TWA)	98 mg/m ³
CK (OEL STEL)	246 mg/m ³
Remark	b (Bőrön át is felszívódik), i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármat); EU1 (2000/39/EK irányelvben közölt érték); T (Azok az anyagok, amelyek egészségkárosító hatása TARTÓS expozíciót követően jelentkezik)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről

Ireland - Occupational Exposure Limits

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Local name	2-Butoxyethanol (EGBE) [Ethylene glycol monobutyl ether]
OEL TWA [1]	98 mg/m ³
OEL TWA [2]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021

Butyl Glycol (111-76-2)

Ireland - Biological limit values

Local name	2-Butoxyethanol
BMGV	200 mg/g creatinine Parameter: BAA - Medium: urine - Sampling time: End of shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)

Italy - Occupational Exposure Limits

Local name	Butossietanolo-2
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	Cute
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.

Latvia - Occupational Exposure Limits

Local name	2-Butoksietanols, (etilēnglikola monobutilēteris, Butilcelosolvs)
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	Āda
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Lithuania - Occupational Exposure Limits	
Local name	Etilenglikolio monobutileteris (butilglikolis, 2-butoksietanolis)
IPRV (OEL TWA)	50 mg/m ³
IPRV (OEL TWA) [ppm]	10 ppm
TPRV (OEL STEL)	100 mg/m ³
TPRV (OEL STEL) [ppm]	20 ppm
Remark	O (medžiaga į organizmą gali prasiskverbti pro nepažeistą odą)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	2-Butoxyéthanol
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	Peau
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	2-Butoxyethanol
Butyl Glycol (111-76-2)	
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	Skin # Gilda
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
Netherlands - Occupational Exposure Limits	
Local name	2-Butoxyethanol
TGG-8u (OEL TWA)	100 mg/m ³
TGG-15min (OEL STEL)	246 mg/m ³

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2022
Poland - Occupational Exposure Limits	
Local name	2-Butoksyetanol (butoksyetylowy alkohol)
NDS (OEL TWA)	98 mg/m ³
NDSCh (OEL STEL)	200 mg/m ³
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	2-Butoxietanol (EGBE)
OEL TWA [ppm]	20 ppm
Remark	A3 (Agente carcinogénico confirmado nos animais de laboratório com relevância desconhecida no Homem); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Portugal - Biological Exposure Indices	
Local name	2-Butoxietanol (EGBE)
BEI	200 mg/g creatinine Parâmetro: Ácido butoxiacético (BAA) - Meio: urina - Momento da amostragem: Fim do turno - Notação: Com hidrólise
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	2-Butoxietanol/Etilenglicol monobutileter
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	P - posibilitatea unei penetrări cutanate importante
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)

Butyl Glycol (111-76-2)

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Serbia - Occupational Exposure Limits	
Local name	2-бутоксиетанол
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	ЕУ* – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2000/39/ЕЗ (прва листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovakia - Occupational Exposure Limits	
Local name	2-Butoxyetanol (butylglykol)
NPHV (OEL TWA) [1]	98 mg/m ³
NPHV (OEL TWA) [2]	20 ppm
NPHV (OEL STEL)	246 mg/m ³
NPHV (OEL STEL) [ppm]	50 ppm
Remark	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	2-butoksietanol (butilglikol)
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Slovenia - Biological limit values	
Local name	2-butoksietanol
BLV	150 mg/g creatinine Parameter: butoksiocetna kislina (po hidrolizi) - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene, pri dolgotrajni izpostavljenosti: ob koncu delovne izmene po več zaporednih delavnikih

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	2-Butoxietanol (Butil cellosolve; Éter monobutílico del etilenglicol)
VLA-ED (OEL TWA) [1]	98 mg/m ³
VLA-ED (OEL TWA) [2]	20 ppm
VLA-EC (OEL STEL)	245 mg/m ³
VLA-EC (OEL STEL) [ppm]	50 ppm

Butyl Glycol (111-76-2)	
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), VLB [®] (Agente químico que tiene Valor Límite Biológico).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Spain - Biological limit values	
Local name	2-Butoxietanol (Butil cellosolve; Éter monobutílico del etilenglicol)
BLV	200 mg/g creatinine Parámetro: Ácido butoxiacético - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: Con hidrólisis
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
Local name	Etylenglykolmonobutyleter (2-Butoxietanol)
NGV (OEL TWA)	50 mg/m ³
NGV (OEL TWA) [ppm]	10 ppm
KTV (OEL STEL)	246 mg/m ³
KTV (OEL STEL) [ppm]	50 ppm
Remark	H (Ämnet kan lätt upptas genom huden. Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	2-Butoxyethanol
WEL TWA (OEL TWA) [1]	123 mg/m ³
WEL TWA (OEL TWA) [2]	25 ppm

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

WEL STEL (OEL STEL)	246 mg/m ³
WEL STEL (OEL STEL) [ppm]	50 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	2-Butoxyethanol
BMGV	240 mmol/mol Creatinine Parameter: butoxyacetic acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	2-Bútoxýetanól (bútýlglykól, bútýlsellósov, etýlenglykólmonóbútýleter, glykólmonóbútýleter)
OEL TWA	100 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	246 mg/m ³
OEL STEL [ppm]	50 ppm

Butyl Glycol (111-76-2)	
Remark	H (efnið getur auðveldlega borist inn í líkamann gegnum húð)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	2-butoksyetanol (Butylglykol; Etylenglykolmonobutyleter)
Grenseverdi (OEL TWA) [1]	50 mg/m ³
Grenseverdi (OEL TWA) [2]	10 ppm
Remark	H: Kjemikalier som kan tas opp gjennom huden; E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	2-бутоксиетанол (бутилгликол)
OEL TWA	98 mg/m ³
OEL TWA [ppm]	20 ppm

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

KTV	2.5
Short time value [mg/m ³]	245 mg/m ³
Short time value [ppm]	50 ppm
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (K) својство на полесно пренесување на супстанците во организмот преку кожата; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)

Switzerland - Occupational Exposure Limits

Local name	2-Butoxyéthanol / 2-Butoxyethanol [Butylglykol, Ethylenglykolmonobutylether]
MAK (OEL TWA) [1]	49 mg/m ³
MAK (OEL TWA) [2]	10 ppm
KZGW (OEL STEL)	98 mg/m ³
KZGW (OEL STEL) [ppm]	20 ppm
Critical toxicity	VRS, Yeux / OAW, Auge
Notation	R, SS _C , B / H, SS _C , B
Remark	INRS, HSE, NIOSH
Regulatory reference	www.suva.ch, 28.03.2022

Switzerland - BAT

Local name	2-Butoxyéthanol / 2-Butoxyethanol
------------	-----------------------------------

Butyl Glycol (111-76-2)

BAT	150 mg/g creatinine (Paramètre biologique: Acide 2-butoxyacétique (après hydrolyse); Substrat d'examen: Urine; Moment du prélèvement: Fin de l'exposition, de la période de travail. Exposition de longue durée: après plusieurs périodes de travail.) / (Biologischer Parameter: 2-Butoxyessigsäure (nach Hydrolyse); Untersuchungsmaterial: Urin; Probennahmezeitpunkt: Expositionsende, bzw. Schichtende. Bei Langzeitexposition: nach mehreren vorangegangenen Schichten.)
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte

Sodium Dioctyl Sulphosuccinate (577-11-7)

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Romania - Occupational Exposure Limits

Local name	2 Etilhexil-sulfo-succinat de sodiu
OEL STEL	20 mg/m ³
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection: Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Appearance	: Liquid.
Colour	: amber.
Odour	: slight.
Odour threshold	: No data available
pH	: 5.5 – 7.5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 68 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.95 – 1.05
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

Superdispersant-25 [®]	
ATE CLP (dust,mist)	2.5 mg/l/4h

Butyl Glycol (111-76-2)	
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961

Sodium Dioctyl Sulphosuccinate (577-11-7)	
LD50 dermal rabbit	> 10000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation : Causes skin irritation.
pH: 5.5 – 7.5
Serious eye damage/irritation : Causes serious eye irritation.
pH: 5.5 – 7.5
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Sodium Dioctyl Sulphosuccinate (577-11-7)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Butyl Glycol (111-76-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Sodium Dioctyl Sulphosuccinate (577-11-7)	
---	--

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	---

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

Butyl Glycol (111-76-2)	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)

12/12/2022 (Issue date)

Butyl Glycol (111-76-2)	
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

Sodium Dioctyl Sulphosuccinate (577-11-7)	
LC50 - Fish [1]	49 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport Not applicable
Transport by sea
Not applicable

Air transport
Not applicable

Inland waterway transport
Not applicable

Rail transport
Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

Denmark

Class for fire hazard	: Class III-1
Store unit	: 50 liter
Classification remarks	: Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK)	: LK 6.1 - Toxic materials
--------------------	----------------------------

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number

Abbreviations and acronyms:

EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet

Superdispersant-25[®]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Full text of H- and EUH-statements:

Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.